



Protect a high speed network from noise and electromagnetic interference when connecting with our Snagless Shielded Cat6 patch cable. For voice/data/video distribution, this cable will handle bandwidth-intensive applications and drastically reduces both impedance and structural return loss (SRL). Each patch cable is fully tested to meet ANSI/TIA 568 C.2 Cat6 component requirements. Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality cable and plugs, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code a network installation. Individual length label on each cable for ease of use.

Features & Benefits

Designed for network adapters, hubs, switches,
routers, HDBaseT applications and moreSupports 10 Gigabit networks up to 180ft for fast data transmission and
maximum performance and supports 1 Gigabit up to 328ftMeets the ANSI/TIA-568-C.2 Cat6 requirements for
supporting a wide variety of applicationsConstructed with shielded twisted pair (STP) wires, designed to protect a
high speed network from noise and electromagnetic interferenceSnagless connector design for high density
environments and protecting the RJ-45 connector's
lockAvailable in a variety of colors to color-code a network

Specifications

General Info

| Product Line | C2G | Color | Yellow | |
|-----------------------|---------------------------|--------------------|--|--|
| UPC Number | 757120008682 | Country Of Origin | Vietnam | |
| Features | PoE (Power Over Ethernet) | Application Sector | Commercial, Industrial, Residential | |
| Warranty Type | Lifetime | Туре | Cable | |
| Dimensions | | | | |
| Product Length US | 10.0 FT | Cable Length | 10 ft | |
| Technical Information | | | | |
| Jacket Material | PVC (Polyvinyl Chloride) | Wire Gauge | 26 AWG | |

| Cable Type | Booted, Ethernet Patch Cable, Shielded (STP), Snagless | Jacket Rating | Standard / Non-Rated |
|----------------|---|---------------|----------------------|
| Cable Diameter | 6.2 mm | Adapter Rear | RJ-45 Male |
| Adapter Front | RJ-45 Male | | |