



Protect a high speed network from noise and electromagnetic interference when connecting with our Snagless Shielded Cat6 patch cable. For voice/data/video distribution, this cable will handle bandwidth-intensive applications and drastically reduces both impedance and structural return loss (SRL). Each patch cable is fully tested to meet ANSI/TIA 568 C.2 Cat6 component requirements.

Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality cable and plugs, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code a network installation. Individual length label on each cable for ease of use.

Features & Benefits

Designed for network adapters, hubs, switches, routers, HDBaseT applications and more	Supports 10 Gigabit networks up to 180ft for fast data transmission and maximum performance and supports 1 Gigabit up to 328ft
Meets the ANSI/TIA-568-C.2 Cat6 requirements for supporting a wide variety of applications	Constructed with shielded twisted pair (STP) wires, designed to protect a high speed network from noise and electromagnetic interference
Snagless connector design for high density environments and protecting the RJ-45 connector's lock	Available in a variety of colors to color-code a network

Specifications

General Info

Product Line	C2G	Color	Orange		
UPC Number	757120008767	Country Of Origin	Vietnam		
Features	PoE (Power Over Ethernet)	Application Sector	Commercial, Industrial, Residential		
Warranty Type	Lifetime	Туре	Cable		
Dimensions					
Product Length US	1.0 FT	Cable Length	1 ft		
Technical Information					
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	26 AWG		

Cable Type	Booted, Ethernet Patch Cable, Shielded (STP), Snagless	Jacket Rating	Standard / Non-Rated
Cable Diameter	6.2 mm	Adapter Rear	RJ-45 Male
Adapter Front	RJ-45 Male		