

The Cat5e Snagless Unshielded (UTP) Slim Network Patch Cable is the perfect solution for high density datacenter applications. The use of 28 AWG conductors allows for a 28% reduction in diameter over a standard Cat5e network patch cable. This reduced diameter provides a smaller cable surface area which allows for increased airflow when compared to standard Cat5e cables. The 28 AWG conductors also allow this cable to have a smaller bend radius than standard Cat5e cables. The small size and small bend radius of this cable allows it to be easily routed through cable management panels.

This cable is designed for fast Ethernet networks that require bandwidth-intensive voice, data, or video distribution applications. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. The molded, snagless boot prevents unwanted cable snags during installation and provides extra strain relief. Available in a variety of colors to easily color-code your network installation.

Note:

- This patch cable does not meet the recommend conductor size, 22-26AWG, requirement of ANSI/TIA-568-C.2. Attenuation is increased due to the smaller 28AWG conductors.

Maximum cable length recommendations:

- 96 Meter Channel (90 meters of horizontal cable and up to 6 meters of slim network patch cables)
- 93 Meter Channel (83 meters of horizontal cable and up to 10 meters of slim network patch cables)
- For POE/POE+ applications we limit bundles to 40 cables due to heat dissipation of these reduced diameter cables.



## Features & Benefits

28% reduction in diameter compared to standard Cat5e cables

Snagless connector design

Meets the ANSI/TIA-568-C.2 standard for Patch Cord Performance

28AWG conductor construction

## Specifications

### General Info

Product Line	C2G	Replaced by Part Number	01103
Color	Black	UPC Number	757120010593
Country Of Origin	Vietnam	Application Sector	Commercial, Industrial, Residential
Type	Cable		

### Dimensions

Product Length US	4.0 FT	Cable Length	4 ft
-------------------	--------	--------------	------

---

Outside Diameter	3.8 mm
------------------	--------

---

### Listing Agencies / 3rd Party Agencies

---

CE Certified	Yes	REACH Compliant	Yes
--------------	-----	-----------------	-----

---

### Additional Information

---

RoHS Compliant	Yes
----------------	-----

---

### Technical Information

---

Jacket Material	PVC (Polyvinyl Chloride)	Category Performance Rating	Cat 5e
Wire Gauge	28 AWG	Shielded/Unshielded	Unshielded
Conductor	4-Pair Twisted	Shield Type	UTP
Cable Type	Ethernet Patch Cable	Jacket Rating	Standard / Non-Rated
Cable Diameter	3.8 mm	Connector Type	Booted, Slim, Snagless
Indoor/Outdoor	Indoor	Connector 2	RJ-45 Male
Connector 1	RJ-45 Male	Insulation Material	HDPE (High-density Polyethylene)

---