



This OM4 Duplex Multimode Fiber Optic Cable is ideal for connecting 40GBase BiDi 10GBaseSR, SFP+ and QSFP+ transceivers for 40 and 10 Gigabit network connections. This cable provides backward compatibility with existing 50/125 equipment and the performance headroom required to support LED and VCSEL laser light sources, and 40 or 10 gigabit Ethernet applications in a datacenter or wiring closet..

Features & Benefits

Constructed to support OM4 transmission standards

Multimode fiber construction - 50/125 diameter core and cladding

Support for 10 Gigabit and 40 Gigabit Ethernet communication

Specifications

General Info

| | | | |
|--------------------|------------------------|-------------------|-----------|
| Product Line | C2G | Color | Aqua |
| UPC Number | 757120011460 | Country Of Origin | Hong Kong |
| Application Sector | Commercial, Industrial | Warranty Type | Lifetime |
| Type | Cable | | |

Dimensions

| | | | |
|-------------------|---------|--------------|-------|
| Product Length US | 23.0 FT | Cable Length | 23 ft |
|-------------------|---------|--------------|-------|

Listing Agencies / 3rd Party Agencies

| | |
|--------------|-----|
| CE Certified | Yes |
|--------------|-----|

Technical Information

| | | | |
|------------------------|----------------|-----------------|--------------------------|
| Fiber Optic Cable Type | Multimode, OM4 | Jacket Material | PVC (Polyvinyl Chloride) |
| Jacket Application | Riser Rated | Bend Radius | 10 mm |
| Simplex/Duplex | Duplex | Cable Type | Fiber Optic |

| | | | |
|--------------------|-----------------------|----------------|------------------|
| Jacket Rating | FT4 Rated, OFNR Rated | Cable Diameter | 2 mm |
| Data Transfer Rate | 40 Gbps | Adapter Rear | SC Male, SC Male |
| Adapter Front | LC Male, LC Male | Fiber Size | 50/125 |
