



For fast Ethernet and Gigabit computer networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat6 TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.

Features & Benefits

Designed for network adapters, hubs, switches, routers, HDBaseT applications and more

Supports 10 Gigabit networks up to 180ft for fast data transmission and maximum performance and supports 1 Gigabit up to 328ft

Meets all Cat6 TIA/EIA requirements for supporting Constructed with unshielded twisted pair (UTP) wires, designed to counter a wide variety of applications EMI, RFI, and crosstalk

Available in a variety of colors to color-code a network

Specifications

General Info

Product Line	C2G	Color	Orange		
UPC Number	757120042075	Country Of Origin	Vietnam		
Features	PoE (Power Over Ethernet)	Application Sector	Commercial, Industrial, Residential		
Warranty Type	Lifetime	Туре	Cable		
Dimensions					
Product Length US	50.0 FT	Cable Length	50 ft		
Technical Information					
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG		

Cable Type	Ethernet Patch Cable, Unbooted, Unshielded (UTP)	Jacket Rating	Standard / Non-Rated
Cable Diameter	6 mm	Adapter Rear	RJ-45 Male
Adapter Front	RJ-45 Male		