

C2G 4ft (1.2m) Cat6 Non-Booted Unshielded (UTP) Ethernet Network Patch Cable - Pink Part No. CG-04256



For fast Ethernet and Gigabit computer networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat6 TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.

Features & Benefits

Designed for network adapters, hubs, switches, routers, HDBaseT applications and more

Meets all Cat6 TIA/EIA requirements for supporting a wide variety of applications

Available in a variety of colors to color-code a network

Supports 10 Gigabit networks up to 180ft for fast data transmission and maximum performance and supports 1 Gigabit up to 328ft

Constructed with unshielded twisted pair (UTP) wires, designed to counter EMI, RFI, and crosstalk

Specifications

General Info				
Product Line	C2G	Replaced by Part Number	04088, 04046	
Color	Pink	UPC Number	757120042563	
Country Of Origin	China	Features	PoE (Power Over Ethernet)	
Application Sector	Commercial, Industrial, Residential	Туре	Cable	
Dimensions				
Product Length US	4.0 FT	Cable Length	4 ft	
Technical Information				
Jacket Material	PVC (Polyvinyl Chloride)	Category Performance Rating	Cat 6	

Wire Gauge	24 AWG	Shielded/Unshielded	Unshielded
	2471110		Onsinetaca
Shield Type	UTP	Cable Type	Ethernet Patch Cable
Jacket Rating	Standard / Non-Rated	Cable Diameter	6 mm
Connector Type	Non-booted	Indoor/Outdoor	Indoor
Connector 2	RJ-45 Male	Connector 1	RJ-45 Male