



For fast Ethernet networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat5e TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.

## Features & Benefits

Designed for network adapters, hubs, switches, routers and moreConstructed with unshielded twisted pair wiresAvailable in 10 colors to color-code a networkAvailable in lengths up to 150ftCMG In-Wall Rated JacketCMG In-Wall Rated Jacket

## Specifications

## General Info

| Jacket Material       | PVC (Polyvinyl Chloride) | Category Performance Rating | Cat 5e                                 |
|-----------------------|--------------------------|-----------------------------|--|
| Technical Information |                          |                             |  |
| Outside Diameter      | 5.3 mm                   |                             |  |
| Product Length US     | 7.0 FT                   | Cable Length                | 7 ft                                   |
| Dimensions            |                          |                             |  |
| Туре                  | Cable                    |                             |  |
| Country Of Origin     | China                    | Application Sector          | Commercial, Industrial,<br>Residential |
| Color                 | Yellow                   | UPC Number                  | 757120226888                           |
| Product Line          | C2G                      | Replaced by Part Number     | 04175                                  |
|                       |                          |                             |  |

| Wire Gauge     | 24 AWG               | Shielded/Unshielded | Unshielded           |
|----------------|----------------------|---------------------|----------------------|
| Conductor      | 4-Pair Twisted       | Shield Type         | UTP                  |
| Cable Type     | Ethernet Patch Cable | Jacket Rating       | Standard / Non-Rated |
| Cable Diameter | 5.3 mm               | Connector Type      | Non-booted           |
| Indoor/Outdoor | Indoor               | Connector 2         | RJ-45 Male           |
| Connector 1    | RJ-45 Male           |                     |                      |