



For fast Ethernet networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat5e TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.

Features & Benefits

Designed for network adapters, hubs, switches, routers and moreConstructed with unshielded twisted pair wiresAvailable in 10 colors to color-code a networkAvailable in lengths up to 150ft

CMG In-Wall Rated Jacket

Specifications

General Info

Product Line	C2G	Color	Blue	
UPC Number	757120251514	Country Of Origin	China	
Application Sector	Commercial, Industrial, Residential	Warranty Type	Lifetime	
Туре	Cable			
Dimensions				
Product Length US	2.0 FT	Cable Length	2 ft	
Technical Information				
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG	
Cable Type	Ethernet Patch Cable, Unbooted, Unshielded (UTP)	Jacket Rating	Standard / Non-Rated	

Cable Diameter	5.3 mm	Adapter Rear	RJ-45 Male
Adapter Front	RJ-45 Male		