



This precision-engineered cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). The DVI-D dual link configuration provides enough bandwidth for resolutions up to 2560x1600 pixels and allows high speed digital video transmission up to 9.9 Gbps. 28 AWG copper conductors are individually insulated in foam-polypropylene to minimize crosstalk, and ensure high speed, error-free transmission.

Tri-shielded undermold with dual foil shield and braid shield protects against unwanted EMI/RFI interference. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: white

Please Note: Does not support analog video; only supports digital video signal.

## Features & Benefits

24-pin digital video cable with transfer rates up to 9.9 Gbps    Perfect for connecting digital displays and projectors to a PC  
Available in lengths up to 5m

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120269113	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

### Dimensions

Product Length US	6.6 FT	Cable Length	6.6 ft
-------------------	--------	--------------	--------

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	28 AWG
Video Resolution	WQXGA (2560x1600)	Cable Type	Video

Jacket Rating	Standard / Non-Rated	Cable Diameter	7 mm
Data Transfer Rate	9.9 Gbps	Adapter Rear	DVI-D Dual Link Male
Adapter Front	DVI-D Dual Link Male		