



This precision-engineered cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). The DVI-D dual link configuration provides enough bandwidth for resolutions up to 2048 x 1536 pixels and allows high speed digital video transmission up to 9.9 Gbps. 28 AWG copper conductors are individually insulated in foam-polypropylene to minimize crosstalk, and ensure high speed, error-free transmission.

Tri-shielded undermold with dual foil shield and braid shield protects against unwanted EMI/RFI interference. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: white

Please Note: Does not support analog video; only supports digital video signal.

Features & Benefits

24-pin digital video cable with transfer rates up to 9.9 Gbps Perfect for extending a DVI-D cable for better projector or display placement

Available in lengths up to 5m

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120269137	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

Dimensions

Product Length US	3.3 FT	Cable Length	3.3 ft
-------------------	--------	--------------	--------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	28 AWG
Video Resolution	WQXGA (2560x1600)	Cable Type	Extension, Video

Jacket Rating	Standard / Non-Rated	Cable Diameter	7 mm
Data Transfer Rate	9.9 Gbps	Adapter Rear	DVI-D Dual Link Female
Adapter Front	DVI-D Dual Link Male		
