



This precision-engineered cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). The DVI-I dual link configuration provides enough bandwidth for resolutions up to 2560 x 1600. Three analog 30 AWG coaxial lines enable high speed analog transmission.

Tri-shielded undermold and braid shield protects against unwanted EMI/RFI interference. Each coax line is individually wrapped in foam-polyolefin insulation and overwrapped with a braided tinned copper shield. 28 AWG copper conductors are individually insulated in hard-density polypropylene to minimize crosstalk, and ensure high speed, error-free transmission. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: white.

Features & Benefits

24-pin cable supports digital and analog transmission

Perfect for connecting digital displays and projectors to a PC

Available in lengths up to 5m

Specifications

General Info

| | | | |
|--------------------|-------------------------|-------------------|----------|
| Product Line | C2G | Color | Black |
| UPC Number | 757120269496 | Country Of Origin | China |
| Application Sector | Commercial, Residential | Warranty Type | Lifetime |
| Type | Cable | | |

Dimensions

| | | | |
|-------------------|--------|--------------|--------|
| Product Length US | 9.8 FT | Cable Length | 9.8 ft |
|-------------------|--------|--------------|--------|

Technical Information

| | | | |
|------------------|--------------------------|--------------|----------------------|
| Jacket Material | PVC (Polyvinyl Chloride) | Wire Gauge | 30 AWG |
| Video Resolution | UXGA (1600x1200) | Cable Type | Video |
| Jacket Rating | Standard / Non-Rated | Adapter Rear | DVI-I Dual Link Male |

