

## C2G

# 2-Port USB 1.1 Over Cat5 Superbooster<sup>TM</sup> Extender Wall Plate Receiver

Part No. CG-29345



The overall plug-and-play solution consists of this wall plate receiver, and your choice of a compatible transmitter that is sold separately: the wall plate (#29344), the dongle (#29348) or the keystone insert (#29349). Customize the configuration to your specific needs! This versatility is ideal for applications where you need flexibility at your computer/source side.

The complete solution is connected via a standard Cat5, Cat5E, or Cat6 UTP cable (not included) that provides easy in-wall installation. This delivers a clean, finished look important for homes, classrooms, offices and anywhere you don't want visible cables lying around. Use pre-terminated network cables, or pull unterminated cable and use the included toolless IDC RJ45 connector to terminate your own cable. Because the USB superbooster wall plate is bus-powered, no external power source is required. Compliant with USB specification 1.1.

Input: Two USB Type A Female Output: One RJ45 Female

Please Note: The power demands of devices such as external drives and USB hubs may require the use of external power for proper operation.

Note: If the USB signal is being extended to support an interactive whiteboard, then we recommend using our product



#### Features & Benefits

Extends two USB 1.	1 signal up to	150ft over category	cables Allows for	flexible positioning of	USB peripherals
--------------------	----------------	---------------------	-------------------	-------------------------	-----------------

Patented, Patent No. US 7,741,562

Receiver is built into wall plates

Pair with a wall plate or dongle transmitter for complete solution

## Specifications

### General Info

Product Line C2G Color White

UPC Number	757120293453	Country Of Origin	China		
Application Sector	Commercial, Residential	Warranty Type	5-Year		
Туре	Active Device, Extender, Receiver, Wall Plate				
Dimensions					
Product Width US	1.31 in	Product Depth US	1.34 in		
Product Height US	4.13 in				
Technical Information					
Number of Gangs	1	Data Transfer Rate	12 Mbps		
Adapter Rear	RJ-45 Female	Adapter Front	USB-A Female, USB-A Female		