



This plenum rated OM4 laser-optimized multimode (LOMMF) MPO fiber array cable is ready for deployment in any multimode 50/125 MTP/MPO network and is perfect for installs in plenum space. OM4 is fully backward-compatible with existing OM3 systems. This multimode, MPO fiber cable is comprised of 12 fiber channels within each connector. This high density MPO fiber cable is pinned out in type A format and is comprised of 12 fiber channels within each connector which is perfect when space is limited and makes it possible to run a single cable that automatically terminates 12 fibers in one easy plug-in. The push-pull release mechanism for the MPO connector is easy to engage and disengage, its latch design also prevents the plug from snagging when jumper cables are being routed.

Features & Benefits

| | |
|---|---------------------------------------|
| Type B pinout | No guide pins on either MPO connector |
| The MPO connector has a push pull spring loaded release | Plenum rated (OFNP) Jacket |
| 3mm jacket outer diameter | |

Specifications

General Info

| | | | |
|--------------|--------------|-------------------|-----------|
| Product Line | C2G | Color | Aqua |
| UPC Number | 757120313083 | Country Of Origin | Hong Kong |
| Type | Cable | | |

Dimensions

| | | | |
|-------------------|---------|--------------|-------|
| Product Length US | 32.8 FT | Cable Length | 33 ft |
|-------------------|---------|--------------|-------|

Technical Information

| | | | |
|------------------------|--------------------------|-----------------|--------------------------|
| Fiber Optic Cable Type | MPO, MTP, Multimode, OM4 | Jacket Material | PVC (Polyvinyl Chloride) |
| Jacket Application | Plenum Rated | Jacket Rating | FT6 Rated, OFNP Rated |
| Cable Diameter | 3 mm | | |