

C2G 16.4ft (5m) MTP 9/125 OS1 Single-Mode Fiber Optic Cable (TAA Compliant) (Plenum-Rated) - Yellow Part No. CG-31461



Make MTP/MPO your choice for high density fiber networks; it's specifically designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications. Save time and money with MTP/MPO's increased ease of installation - simply pull one cable rather than twelve. Each MTP/MPO fiber assembly consists of twelve 9/125 Single-mode fibers under one OFNP plenumrated jacket.

With our MTP/MPO, it's possible to run a single cable that automatically terminates twelve fibers in one easy plug-in. Plus, the small form factor of an MTP/MPO connector provides a higher port density. With its push-pull release mechanism, the MTP/MPO connector is easy to engage and disengage. Plus, its latch design prevents the plug from snagging when jumper cables are being routed. Straight-through pinning; immune to electrical interference.

Please Note: MTP/MPO is a registered trademark of US Conec Ltd. Attenuation testing performed in accordance with EIA/TIA-455-171A.

Small form factor provides a higher port density

Features & Benefits

Designed to support gigabit ethernet, fibre channel, ATM, or any application that Plenum rated for cable runs through walls and drop requires high speed data transfer ceilings with plenum air space

Ease of installation - simply pull one cable rather than twelve

Push-pull release mechanism and latch design for easy use

Specifications

General Info

Product Line	C2G	Color	Yellow
UPC Number	757120314615	Country Of Origin	Hong Kong
Application Sector	Commercial, Industrial	Warranty Type	Lifetime
Туре	Cable		
Dimensions			
Product Length US	16.4 FT	Cable Length	16.4 ft
Technical Information			
Fiber Optic Cable Type	MTP, OS1, Single-Mode	Jacket Material	PVC (Polyvinyl Chloride)
Jacket Application	Plenum Rated	Bend Radius	45 mm
Cable Type	Fiber Optic	Jacket Rating	FT6 Rated, OFNP Rated
Cable Diameter	3 mm	Adapter Rear	MTP

Adapter Front	MTP	Fiber Size	9/125