



With LC to MTRJ termination, this high quality fiber optic patch cable is specifically designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications. The small LC and MTRJ connectors satisfy the need for higher port density both in the telecom room and the work area, and offer twice the port density of traditional SC and ST fiber connectors. Both connectors with their RJ-style latch clip design are easy to engage and disengage, and give each connection greater durability in resisting pulls, strains, snags, and impacts during cabling installs and maintenance.

The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 62.5/125 multimode fiber, immune to electrical interference.

## Features & Benefits

Designed to support gigabit ethernet, fibre channel, ATM, or any application that requires high speed data transfer

Patented injection molding process for greater durability

Optically inspected and tested for insertion loss

Pull-proof jacket design, immune to electrical interference

## Specifications

### General Info

|                    |                        |                   |           |
|--------------------|------------------------|-------------------|-----------|
| Product Line       | C2G                    | Color             | Orange    |
| UPC Number         | 757120331148           | Country Of Origin | Hong Kong |
| Application Sector | Commercial, Industrial | Warranty Type     | Lifetime  |
| Type               | Cable                  |                   |           |

### Dimensions

|                   |         |              |         |
|-------------------|---------|--------------|---------|
| Product Length US | 19.7 FT | Cable Length | 19.7 ft |
|-------------------|---------|--------------|---------|

### Technical Information

|                        |                |                 |                          |
|------------------------|----------------|-----------------|--------------------------|
| Fiber Optic Cable Type | Multimode, OM1 | Jacket Material | PVC (Polyvinyl Chloride) |
| Jacket Application     | Riser Rated    | Bend Radius     | 50 mm                    |
| Simplex/Duplex         | Duplex         | Cable Type      | Fiber Optic              |

---

|                    |                       |                |                  |
|--------------------|-----------------------|----------------|------------------|
| Jacket Rating      | FT4 Rated, OFNR Rated | Cable Diameter | 1.8 mm           |
| Data Transfer Rate | 1 Gbps                | Connector 2    | LC Male, LC Male |
| Connector 1        | MTRJ Female           | Fiber Size     | 62.5/125         |

---