



Cost-effective solution that provides higher bandwidth and transmission rates and supports longer distances with lower loss than 62.5/125 fiber. Specifically designed for use with today's narrower aperture components, this cable is fully compatible with multimode applications. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 50/125 multimode fiber, immune to electrical interference.

Features & Benefits

OM2 - 50µm core

Supports 500 MHz km OFL at 850/1300nm

OFNR - Riser rated jacket

Tested in accordance with EIA/TIA-455-171A

Specifications

General Info

Product Line	C2G	Color	Red
UPC Number	757120373797	Country Of Origin	China
Application Sector	Commercial, Industrial	Warranty Type	Lifetime
Type	Cable		

Dimensions

Product Length US	32.8 FT	Cable Length	33 ft
-------------------	---------	--------------	-------

Technical Information

Fiber Optic Cable Type	Multimode, OM2	Jacket Material	PVC (Polyvinyl Chloride)
Jacket Application	Riser Rated	Bend Radius	50 mm
Simplex/Duplex	Duplex	Cable Type	Fiber Optic
Jacket Rating	FT4 Rated, OFNR Rated	Data Transfer Rate	10 Gbps

Connector 2

LC Male

Connector 1

LC Male

Fiber Size

50/125
