



C2G
3.3ft (1m) LC-LC 62.5/125 OM1 Duplex Multimode Fiber Optic Cable - Plenum CMP-Rated - Orange
Part No. CG-37955



With LC to LC termination, this high quality fiber optic patch cable is specifically designed for ethernet, multimedia, or communication applications. The small LC connector [B]takes HALF the size of traditional SC and ST fiber connectors,[/B] since it offers twice the port density of conventional SC and ST connectors to satisfy the need for higher port density in telecom closets, equipment rooms, and work areas.

The LC connector's RJ-style latch clip design gives each connection greater durability in resisting snagging, pulls, strains and impacts during cabling installs and maintenance. Plus, it is easy to engage and disengage with the "telephone jack style" release mechanism. The plenum rating provides the fire protection required to run this cable within walls and air plenums without using conduit.

The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 62.5/125 multimode fiber, immune to electrical interference.

Features & Benefits

Designed to support gigabit ethernet, FDDI, multimedia, ATM, or any application that requires high speed data transfer

Plenum CMP rated for cable runs through walls and drop ceilings with plenum air space

Patented injection molding process for greater durability

Optically inspected and tested for insertion loss

Pull-proof jacket design, immune to electrical interference

Specifications

General Info

| | | | |
|--------------------|------------------------|-------------------|----------|
| Product Line | C2G | Color | Orange |
| UPC Number | 757120379553 | Country Of Origin | China |
| Application Sector | Commercial, Industrial | Warranty Type | Lifetime |
| Type | Cable | | |

Dimensions

| | | | |
|-------------------|--------|--------------|--------|
| Product Length US | 3.3 FT | Cable Length | 3.3 ft |
|-------------------|--------|--------------|--------|

Technical Information

| | | | |
|------------------------|----------------|-----------------|--------------------------|
| Fiber Optic Cable Type | Multimode, OM1 | Jacket Material | PVC (Polyvinyl Chloride) |
| Jacket Application | Plenum Rated | Bend Radius | 50 mm |
| Simplex/Duplex | Duplex | Cable Type | Fiber Optic |

| | | | |
|---------------|----------------------|--------------------|---------|
| Jacket Rating | CMP Rated, FT6 Rated | Data Transfer Rate | 1 Gbps |
| Adapter Rear | LC Male | Adapter Front | LC Male |
| Fiber Size | 62.5/125 | | |
