



A high quality BNC cable for video applications including CCTV, broadcast, studio, boardroom presentations, home theater, etc. Manufactured from 75 Ohm RG59/U dual shield coax cable (60% copper braid over foil) with a 22 AWG copper-covered steel center conductor. Finished with bright nickel-plated BNC connectors that have molded PVC strain relief to protect the cable from wear over time.

Features & Benefits

RG59/U Dual Shield coaxial cable

Constructed with a 75copper conductor

Nickel-plated BNC connectors

Molded PVC strain relief

Specifications

General Info

| | | | |
|--------------------|-------------------------------------|-------------------|----------|
| Product Line | C2G | Color | Black |
| UPC Number | 757120400301 | Country Of Origin | China |
| Application Sector | Commercial, Industrial, Residential | Warranty Type | Lifetime |
| Type | Cable | | |

Dimensions

| | | | |
|-------------------|---------|--------------|-------|
| Product Length US | 50.0 FT | Cable Length | 50 ft |
|-------------------|---------|--------------|-------|

Technical Information

| | | | |
|-----------------|--------------------------|---------------|----------------------|
| Jacket Material | PVC (Polyvinyl Chloride) | Wire Gauge | 22 AWG |
| Cable Type | Video | Jacket Rating | Standard / Non-Rated |
| Cable Diameter | 6 mm | Adapter Rear | BNC Male |
| Adapter Front | BNC Male | | |

