

Audio/video installations in educational and commercial settings often require plenum-rated cabling. Our plenum-rated line wasengineered to overcome common challenges faced by installers.

This computer audio/video combination cable is an economic alternative, and saves valuable installation time versus installing and purchasing individual cables. The HD15 connectors are low profile (1.25in total depth) which saves valuable space in the gang box, while the rounded shape (fits 1.25in diameter mounts) accommodates smaller mounts so that the cable can be easily hidden from view. The 3.5mm connectors are also low profile (1.5in total depth) and feature specific breakout lengths to fit your application. The cable is conveniently labeled to identify the 6in breakout for mounting in electrical boxes and the 20in breakout for the display or projector end.

This combination cable is constructed from three 30 AWG coaxial plus one 26 AWG twisted pair to ensure RGBHV signal integrity in your installation. The coax cables feature a tinned copper braid that provides 92% minimum shielding. The audio uses 26 AWG fully-shielded conductors to prevent interference from the RGBHV signal. Overall the cable is well constructed to protect and prevent any EMI/RFI interference, and to ensure that the highest quality signal is transmitted for optimal audio/video performance.

[B]Please Note:[/B] Pin 9 is not loaded. Pin 9 is not required for standard computer video applications.

Features & Benefits

Plenum, CMP-Rated jacket	Rounded connectors for easily installation
Supports up to a 2048x1536 resolution	

Specifications

General Info			
Product Line	C2G	Color	Black
UPC Number	757120401759	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		
Dimensions			
Product Length US	15.0 FT	Cable Length	15 ft
Technical Information			
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
Video Resolution	QXGA (2048x1536)	Jacket Application	Plenum Rated

Cable Type	Audio, Video	Jacket Rating	CMP Rated, FT6 Rated
Adapter Rear	VGA Male, 3.5mm Stereo Male	Adapter Front	3.5mm Stereo Male, VGA Male