



C2G
50ft (15.2m) 3.5mm Stereo Audio Cable with Low Profile Connectors M/M - Plenum CMP-Rated
Part No. CG-40518



Audio/video installations in educational and commercial settings often require plenum-rated cabling. Our plenum-rated line was engineered to overcome common challenges faced by installers. Low-profile connectors (1.5in total depth) save valuable space and enable easier in-wall connections. And our small-diameter (0.25in) cable design further reduces the space and clearance required to run the necessary cabling through walls and plenum air spaces.

This cable is constructed from three 75 Ohm coaxial cables using 26 AWG center conductors and featuring a tinned copper braid that provides 92% over foil shield. CMP rating provides the fire protection required to run within walls and air plenums without the need for conduit.

Features & Benefits

Supports a Stereo Audio signal

Plenum, CMP-rated jacket

24 AWG conductor construction

Low profile connectors

Specifications

General Info

Product Line	C2G	UPC Number	757120405184
Country Of Origin	China	Application Sector	Commercial, Residential
Warranty Type	Lifetime	Type	Cable

Dimensions

Product Length US	50.0 FT	Cable Length	50 ft
-------------------	---------	--------------	-------

Technical Information

Jacket Application	Plenum Rated	Cable Type	Audio
Jacket Rating	CMP Rated, FT6 Rated	Cable Diameter	3.4 mm
Adapter Rear	3.5mm Stereo Male	Adapter Front	3.5mm Stereo Male