



C2G Plus Series Slim Flexible HDMI Cable with Low Profile Connectors supports all HDMI 2.0 features\* and is perfect for home theater or desktop audio video applications requiring high speed HDMI features and video resolutions up to 4K (4096 x 2160 at 60Hz, 4:4:4).

The ultra-slim cable construction and the low profile, compact connector design makes this cable an ideal fit for installations in tight spaces. The Ethernet capabilities of the cable allow a user to connect multiple Ethernet enabled HDMI devices through a single Ethernet connection for accessing interactive online content or updating device firmware. This fully-functional, high bandwidth cable is tested to perform at industry standards and is backed by a lifetime warranty.

\*Note: C2G41398 supports HDMI 1.4 features, including resolutions up to 1080p @60Hz

## Features & Benefits

- Supports all HDMI 2.0 features\*, including resolutions up to 4K (4096 x 2160) at 60Hz) which means higher quality video for viewing your screen content
- Ultra-slim cable construction (36 AWG) and low profile connectors, designed for installations in tight spaces
- Supports 32 audio channels for an immersive audio experience
- Supports CEC extensions for control of consumer electronics devices through a single control point
- Gold plated connectors for increased electrical conductivity and enhanced durability
- Backed by a Lifetime Warranty for peace of mind

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120413639	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

### Dimensions

Product Length US	3.0 FT	Cable Length	3 ft
-------------------	--------	--------------	------

### Technical Information

Jacket Material	Flexible PVC	Wire Gauge	36 AWG
Video Resolution	4K	Bend Radius	25.4 mm
Cable Type	High Speed HDMI, Ultra-Flexible, Video	Jacket Rating	VW-1 Rated
Cable Diameter	3.6 mm	Data Transfer Rate	18 Gbps
Signal	HDMI 2.0	Adapter Rear	HDMI Male

---

Adapter Front

HDMI Male

---