

12ft (3.7m) Select VGA Video Cable M/M - In-Wall CMG-Rated Part No. CG-50214



The C2G Select VGA Video Cable is perfect for source to display connectivity for in-home desktop or in-wall commercial applications which require video resolutions of up to QXGA (2048x1536). The CMG rated jacket provides a solution for in-wall applications, while the low-profile, rounded connectors make installing in tight spaces, such as a projector mount pole, easy. This cable is designed to support high resolution video applications over long distances of up to 150ft. All 15 pins are wired providing support for DDC2 (E-DDC) and Extended Display Identification Data (EDID) signals, i.e. communication of the display's capabilities, ensuring that the content from the source is sent at the optimal resolution for the display.

Features & Benefits

In-wall, CMG-rated jacket Supports up to a 2048x1536 resolution All 15 pins wired to support DDC2 (E-DDC) and EDID Low profile connectors

| Specifications | | | | |
|-----------------------|--------------------------|--------------------|---------------|--|
| General Info | | | | |
| Product Line | C2G | Color | Black | |
| UPC Number | 757120502142 | Country Of Origin | China | |
| Application Sector | Commercial, Residential | Warranty Type | Lifetime | |
| Туре | Cable | | | |
| Dimensions | | | | |
| Product Length US | 12.0 FT | Cable Length | 12 ft | |
| Technical Information | | | | |
| Jacket Material | PVC (Polyvinyl Chloride) | Wire Gauge | 30 AWG | |
| Video Resolution | QXGA (2048x1536) | Jacket Application | In-Wall Rated | |
| Bend Radius | 51 mm | Cable Type | Video | |

| Jacket Rating | CMG Rated, FT4 Rated | Cable Diameter | 8.5 mm |
|---------------|----------------------|----------------|----------|
| Adapter Rear | VGA Male | Adapter Front | VGA Male |
| Voltage | 30.0 V | | |