

15ft (4.6m) Serial RS232 DB9 Null Modem Cable with Low Profile Connectors WF - In-Wall CMG-Rated

Part No. CG-52187

Audio/video installations in educational and commercial settings often require in-wall rated cable. Our CMG-rated line was specifically engineered to meet this requirement while overcoming common challenges faced by installers in these environments.



This computer audio/video combination cable is an economic alternative, and saves valuable installation time versus installing and purchasing individual cables. The HD15 connectors are low profile (1.25in total depth) which saves valuable space in the gang box, while the rounded shape (fits 1.25in inner diameter mounts) accommodates smaller mounts so that the cable can be easily hidden from view. The 3.5mm connectors are also low profile (1.5in total depth) and feature specific breakout lengths to fit your application. The cable is conveniently labeled to identify the 6in breakout for mounting in electrical boxes and the 20in breakout for the display or projector end.

This combination cable is constructed from three 30 AWG coaxial cables plus one 26 AWG twisted pair to ensure RGBHV signal integrity in your installation. The coax cables feature a tinned copper braid that provides 92% minimum shielding. The audio uses 26 AWG fully-shielded conductors to prevent interference from the RGBHV signal. Overall the cable is well constructed to protect and prevent any EMI/RFI interference, and to ensure that the highest quality signal is transmitted for optimal audio/video performance.

Please Note: Pin 9 is not loaded. Pin 9 is not required for standard computer video applications.

Features & Benefits

- Catales & Bellelli				
Designed to support RS-232/Serial communications Shielded to prevent unwanted EMI/RFI interference		CMG-rated for in-wall us	CMG-rated for in-wall use	
		Connector thumbscrews for a quick and easy connection		
Specifications				
General Info				
Product Line	C2G	Color	Black	
UPC Number	757120521877	Country Of Origin	Vietnam	
Features	RS232	Application Sector	Commercial, Industrial, Residential	
Warranty Type	Lifetime	Туре	Cable	
Dimensions				
Product Length US	15.0 FT	Cable Length	15 ft	
Technical Information				
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	28 AWG	
Jacket Application	In-Wall Rated	Cable Type	Modem, Serial	
Jacket Rating	CMG Rated, FT4 Rated	Adapter Rear	DB9 Female	
Adapter Front	DB9 Male			