

The 3.5mm Male 3 Position TRS to Female XLR Cable is perfect for interconnecting devices with 3.5mm jacks and devices with XLR inputs — making it ideal for mixing consoles, amplifiers, and powered speakers.



This audio cable includes a 3.5mm TRS (Tip/Ring/Sleeve) connector, which means this cable has three conductors or three poles, including left and right stereo channels. The 3.5mm TRS jacks are commonly found on most stereo audio devices, while XLR inputs are commonly found on mixing consoles, amplifiers, and powered speakers. This is an unbalanced cable, so the left and right channels are soldered together making a mono signal to XLR, allowing the left and right stereo signal from a source with a 3.5mm stereo output to be converted to a single mono feed.

This audio cable has 22 AWG conductors, insulated, under an aluminum foil shield, and covered by a soft PVC shell. The soft PVC jacket reduces the risk of the cable kinking and damaging the conductors. Enjoy lasting quality and excellent performance no matter the connection.

Features & Benefits

Three poles/conductors for TRS jacks found on microphones and stereo audio devices	Unbalanced cable, the Left and Right channels are soldered together
XLR input for mixing consoles, amplifiers, and powered speakers	Lifetime warranty, for peace of mind

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120414681	Country Of Origin	Vietnam
Application Sector	Residential	Warranty Type	Lifetime
Type	Cable		

Dimensions

Product Length US	1.5 FT	Cable Length	1.5 ft
-------------------	--------	--------------	--------

Technical Information

Jacket Material

PVC (Polyvinyl Chloride)

Wire Gauge

22 AWG

Cable Type

Audio

Adapter Rear

XLR 3-pin Female

Adapter Front

3.5mm Male
